



1. 1/8" (3 mm) S.S. cable tether attached to bolt and davit arm.
2. 6" I-beam adjustment holes
3. 3/4" (19 mm) dia. aluminum handles.
4. 1/4" (6 mm) gusset plate welded to beam.
5. 3/8" (10 mm) thickness sliding S.S. suspension line attachment.
6. Four 1/2" (12 mm) S.S. bolts, lock washers and nuts.
7. 6063-T6 aluminum 3" x 3" x 1/4" (76 mm x 76 mm x 6 mm) brace support 3/4" (19 mm) S.S. bolt extruded aluminum davit arm mast.
8. (5/16" x 8-5/8" O.D. DIA (8 mm x 220 mm) Davit arm mast locking ring.

Davit Arm Base:

9. Steel plate, all hot dip galvanized and urethane insulated to prevent corrosion.
10. Stack Jack Flashing. Available in: Aluminum, copper, or stainless steel.
11. Four 3/4" (19 mm) S.S. bolts, lock washers and nuts.
12. 1/4" x 14" x 14" (6 mm x 356 mm x 356 mm) steel plate.

PROPRIETARY AND CONFIDENTIAL

The information contained in this drawing is the sole property of Rooftop Anchor, Inc. Any reproduction in part or as a whole without written permission of Rooftop Anchor, Inc. is prohibited.

Davit